

ARES 4200

Electric Diaphragm Pump

Electric diaphragm pump with hand trolley for professional high-pressure airless paint spraying, suitable for the light construction sector for medium-large surfaces with medium-low viscosity mural products. It can be used with enamels, lacquers, base coats and varnishes, medium and low viscosity water-based paints.



COD	DESCRIPTION
TKG42G	ARES 4200 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Hand trolley - Manometer - HP hose 7,5m - RST1 spray gun - FM6 tip guard - Reversible
TKG42H	ARES 4200 Electric airless diaphragm pump volt 230/ Hz50 single phase and horizontal C/ Hand trolley - Manometer - Gravity tank

Technical specifications

Motor | Volt: 230 Volt/ 50 Hz

Variant: 380 Volt/ 110 Volt

Power: 0,74 Kw

Max. Delivery Free Flow: ltr/min 4,0

Max. Tip: 1 Gun 0,021

Max. Tip: 2 Guns 0,013

Max. Tip: 3 Guns -----

Max. working outlet pressure: Bar (psi) 200 (2900)

Max length HP hose: mt 60

Max length HP hose (elevation): mt 60

Weight: Kg. 26

Material inlet fitting size: M 36x2 mm

Material outlet fitting size: M 16x1,5mm